



INSULATED BLANK-OFF PANELS
WITH 1" OR 2" INSULATION

NON-INSULATED
BLANK-OFF PANELS

ATTACHMENT

ALUMINUM BLANK-OFF PANELS ARE SECURED
WITH STAINLESS STEEL SHEET METAL SCREWS
SPACED APPROXIMATELY 16" ON CENTER.

OPTIONS

FINISH:

EXTERIOR (LOUVER SIDE) - MILL,
BLACK, MATCH LOUVER

INSULATION:

NONE, 1", 2"

SEALING:

SILICONE CAULK (NON-REMOVABLE)
or NONE

SCREENS:

ALTHOUGH ALL SCREENS ARE
AVAILABLE WITH BLANK-OFFS, THE
PREFERRED MANUFACTURING OPTION
IS NO SCREEN

MATERIAL	DESCRIPTION	SPECIFICATIONS	
		ENG.	METRIC (MM)
1" INSULATION	POLYSTYRENE	1"	25.4mm
2" INSULATION	POLYSTYRENE	2"	50.8mm
BLANK-OFF	.032 ALUMINUM (MILL FINISH & BLACK)	NA	NA
BLANK-OFF	.063 ALUMINUM (PAINTED FINISH)	NA	NA

DUE TO CONTINUING RESEARCH AIROLITE
RESERVES THE RIGHT TO CHANGE
SPECIFICATIONS WITHOUT NOTICE



DRAWN BY: CWC

SCALE: NONE

DATE: 01/11

STANDARD BLANK-OFF PANELS

REV. NO: 0