



FLANGE MAY BE LOCATED AT INTERIOR OR EXTERIOR OF LOUVER TO FIT CONDITIONS

**NOTE:**  
NOT RECOMMENDED FOR USE WITH MIAMI-DADE APPROVED PRODUCTS.

**DESIGNER NOTE:**  
THIS DETAIL IS A CONCEPTUAL DESIGN ILLUSTRATION ONLY. FASTENER SIZE AND SPACING MUST BE DESIGNED TO SPECIFIC APPLICATION REQUIREMENTS. NO WARRANTY OR GUARANTEE IS EXPRESSED OR IMPLIED.

**MATERIAL NOTE:**  
ALUM. LOUVERS - 8 GA.(.125") ALUM.  
GALV. LOUVERS - 16 GA.(.063") GALV. STEEL

HOLES FOR ATTACHMENT TO CONDITIONS (IF REQ'D) DRILLED IN FIELD NOT BY AIROLITE. ANCHORS NOT BY AIROLITE

CONTINUOUS FLAT FLANGE FACTORY WELDED TO LOUVER.

LOUVER



DRAWN BY:

SCALE: NONE

DATE: 04/03

**TYPICAL LOUVER DETAIL:  
METHOD OF INSTALLATION-  
WELDED FLANGE**

REV. NO: 0

FORM NO: 623083