



NOTE:
STANDARD CONSTRUCTION
IS 2 PLATES ON TOP
OF EACH OTHER

SECTION SIZE LIMITS

| | MINIMUM | MAXIMUM |
|--------|----------|-----------------|
| WIDTH | 12" (MM) | 120" * (3048MM) |
| HEIGHT | 12" (MM) | 120" * (3048MM) |

EXTERIOR ELEVATION

* ONE DIMENSION WIDTH OR HEIGHT
MUST NOT EXCEED 48" (1524mm).

SPECIFY REQUIREMENTS
IN SCHEDULE BELOW:

- A - SEE ABOVE
- B - SEE ABOVE
- C - SEE ABOVE
- D - SEE ABOVE
- E - GRILLE DEPTH NO FRAME: SPECIFY
MINIMUM .250"(6.35mm) TO
MAXIMUM 1.00"(25.4mm) DEPTH
- F - GRILLE DEPTH WITH FRAME: SPECIFY
MINIMUM 2"(50.8mm) TO
MAXIMUM 6"(152.4mm) DEPTH
- G - MATERIAL THICKNESS: SPECIFY
MINIMUM 0.025"(0.635mm) TO
MAXIMUM 0.500"(12.7mm) DEPTH
- H - FRAME: SPECIFY
N-NONE
C-ALUMINUM CHANNEL
T-TUBE

GRILLE FINISH

- NATURAL MILL
- PRIME COAT
- BAKED ENAMEL
- KYNAR 500 (2 COAT)
- KYNAR 500 (3 COAT)
- SPECIFY COLOR SELECTION:
- ANODIZE
- 215-R1 ANODIZE
- LIGHT BRONZE
- MEDIUM BRONZE
- DARK BRONZE
- BLACK

INSTALLATION METHOD

- CLIP ANGLES
- HOLES IN PERIMETER
- NONE
- OTHER _____

INSTALLATION FINISH

- NATURAL
- _____

CONSTRUCTION METHOD

ALL-WELDED ASSEMBLY



| ITEM | QTY. | A | B | C | D | E | F | G | H | OPENING SIZE | | GRILLE SIZE | | SECT QTY. | SECTION SIZE | |
|------|------|---|---|---|---|---|---|---|---|--------------|--------|-------------|--------|-----------|--------------|--------|
| | | | | | | | | | | WIDTH | HEIGHT | WIDTH | HEIGHT | | WIDTH | HEIGHT |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |



LOUVER TYPE **SANSOME GRILLE**

MATERIAL: ALUMINUM PLATE

DATE: 4-7-09

REV. NO:

FILE: STD SANSOME

This drawing and the design represented are the confidential and proprietary property of THE AIROLITE COMPANY and may not be disclosed, loaned, copied or used for any purpose other than design review and approval without the expressed written consent of THE AIROLITE COMPANY.