
6766/FCB6766 - RECOMMENDED SPECIFICATION**GENERAL**

Furnish and install where indicated on plans or described in schedules Louver Type 6766 (or FCB6766) as designed and manufactured by The Aiolite Company LLC, Schofield, Wisconsin. Louvers shall be furnished with bird screen, insect screen, supports, installation hardware and finishes as specified and as required for a complete installation.

SUBMITTALS

Manufacturer shall submit shop drawings incorporating key plans, elevations, sections and details showing profiles, angles and spacing of louver blades and frames; unit descriptions related to wall openings and construction; and, anchorage details and locations. Provide samples of manufacturer's finish and color charts showing the fully range of colors available. For each type of product specified, submit free area, air performance, and water penetration ratings. Performance ratings shall be determined in accordance with AMCA Standard 500-L and licensed under the AMCA Certified Ratings Program.

PRODUCTS

Louvers shall be dual drainable Louver Type 6766 with visible vertical mullions (or Louver Type FCB6766 with concealed vertical mullions). Louvers shall be 6-inches (152.4 mm) deep and assembled entirely from galvanized steel components. Blades and frames shall be 16 gauge (0.060") galvanized steel. Blades shall be stationary, incorporate two drainable gutters, and be spaced (5.5)-inches (139.7 mm) on center. Jamb frames shall incorporate two drainable gutters to ensure resistance to water penetration.

STRUCTURAL DESIGN CRITERIA

Manufacturer shall design and furnish all supports required to withstand a wind force of not less than 25 pounds per square foot. Louvers larger than 84-inches wide x 120-inches high will be fabricated and installed in multiple sections. Louvers blades, frames, mullions and anchorages shall be demonstrated to withstand the specified wind design load.

PERFORMANCE RATINGS

FREE AREA:	7.45 Square Feet (0.68 m ²)
MINIMUM FREE AREA VELOCITY	
at Beginning Point of Water Penetration:	1,127 fpm (5.72 m/s)
MINIMUM AIR VOLUME FLOW RATE	
at Beginning Point of Water Penetration:	8,396 cfm (3.89 m ³ /s)
MAXIMUM STATIC PRESSURE	
at Beginning Point of Water Penetration:	0.15 in. H ₂ O (0.037 kPa)